

BRIEF INTRODUCTION

WEIHAI JIAHANG RUBBER TECHNOLOGY CO., LTD. was founded in 1974. As a professional tire manufacturer in Weihai, Shandong, China.

We specialize in a full range of tires, including OTR, industrial, agricultural, trailer, and mobile home tires.

With advanced production equipment, scientific management and perfect quality control system, our products are enjoying a good reputation in overseas market. Our quality products pass all the regular testing. They are certified by USA DOT, REACH, and ISO standards.

Welcome to JIAHANG and sincerely hope to develop a good business with you.

INDEX

OTR TIRE	2-3
OTR GRADER TIRE	4-5
PORT USE TIRE	5
OTR RADIAL TIRE	6
FORTLIFT LIFT TIRE	6
INDUSTRIAL TIRE	7-9
SKID STEER TIRE	10
FARM TIRE	11
IMPLEMENT TIRE	12
AGRICULTURAL TIRE	13-17
AGRICULTURAL RADIAL TIRE	15-16
IRRIGATION TIRE	17
RUBBER MINE TIRE	18
FORESTRY TIRE	19-20
FLOTATION TIRE	20
LPT & MOBILE HOME TIRE	21
TRAILER TIRE	22-24
BIAS TRUCK TIRE	24-26
MINING TIRE	25
UNDERGROUND MINING TIRES	26



ST312



ST818

OTR TIRE E3/L3 / ST312

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
16.00-25	28	TL	11.25	30	38	432	17.0	1493	58.8	575*750	83*109	6700*11500	14800*25400	50*10	30*5
16.00-25	32	TL	11.25	30	38	432	17.0	1493	58.8	625*800	90*116	7200*12100	15875*26675	50*10	30*5
18.00-25	32	TT/TL	13.00	32	40	498	19.6	1617	63.7	575*750	83*109	8750*15000	19300*33100	50*10	30*5
18.00-25	40	TL	13.00	32	40	498	19.6	1617	63.7	700*950	101*138	9700*21385	17000*37480	50*10	30*5
17.5-25	16	TT/TL	14.00/1.5	25.5	32	445	17.5	1348	53.1	300*475	44*69	4250*7300	9350*16100	50*10	30*5
17.5-25	20	TT/TL	14.00/1.5	25.5	32	445	17.5	1348	53.1	400*575	58*83	5000*8250	11000*18200	50*10	30*5
20.5-25	20	TT/TL	17.00/2.0	29	37	521	20.5	1493	58.8	325*450	47*65	6000*9500	13200*20900	50*10	30*5
20.5-25	24	TT/TL	17.00/2.0	29	37	521	20.5	1493	58.8	350*525	51*76	6300*10300	13890*22700	50*10	30*5
23.5-25	20	TT/TL	19.50/2.5	32	40	597	23.5	1617	63.7	300*375	44*54	7300*10900	16100*24000	50*10	30*5
23.5-25	24	TT/TL	19.50/2.5	32	40	597	23.5	1617	63.7	350*475	51*69	8000*12500	17600*27600	50*10	30*5
26.5-25	28	TL	22.00/3.0	35	44	673	26.5	1750	68.9	350*475	51*69	10000*15500	22000*34200	50*10	30*5
29.5-25	28	TL	25.00/3.5	36	45	749	29.5	1874	73.8	325*425	47*62	11500*17500	25400*38600	50*10	30*5

OTR TIRE E3/L3 / ST818

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
23.5-25	20	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	300*375	44*54	7300*10900	16100*24000	50*10	30*5
23.5-25	24	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	350*475	51*69	8000*12500	17600*27600	50*10	30*5



OTR TIRE E3/L3 / ST313

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
23.5-25	20	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	300*375	44*54	7300*10900	16100*24000	50*10	30*5
23.5-25	24	TT/TL	19.50/2.5	31.5	39.5	597	23.5	1617	63.7	350*475	51*69	8000*12500	17600*27600	50*10	30*5

OTR TIRE E3/L3 / ST314

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
14.00-24	24	TT	10.00	25	32	375	14.8	1368	53.9	575	83	5150	11400	50	30

OTR TIRE JY628

Size	P.R.	TT/TL	Rim	Tread	New tire inflated dimensions		Pressure		Max. Load	
					Section Width	Overall Diameter	(kPa)	(psi)	(kg)	(Lbs)
17.5-25	28	TT	14.00/1.5	L5	445	1400	475	69	7300	16100
18.00-25	40	TT	13.00/2.5	L5	495	1615	950	138	17000	37480
20.5-25	20	TT	17.00/2.0	L5	521	1548	450	65	9500	20900
20.5-25	24	TT	17.00/2.0	L5	521	1548	525	76	10300	22700
23.5-25	24	TT	19.50/2.5	L5	595	1675	475	69	12500	27600
23.5-25	28	TT	19.50/2.5	L5	595	1675	550	80	13600	29980
26.5-25	28	TT	22.00/3.0	L5	650	1750	475	69	15500	34200
26.5-25	32	TT	22.00/3.0	L5	650	1750	550	80	17000	37500
29.5-25	28	TT	25.00/3.5	L5	749	1921	425	62	17500	38600
29.5-25	34	TT	25.00/3.5	L5	749	1921	525	76	20000	44090
16/70-16	14	TT	10.00	L5	385	935	280	41	1600	3525
16/70-20	16	TT	13.00	L5	410	1075	300	43.5	3350	7385
20.5/70-16	14	TT	10.00	L5	385	935	280	41	1600	3525



G2/L2-A/ST518

G2/L2-B/ST519

G2/L2-C/ST316

OTR GRADER TIRE G2/L2-A/ST518 , B/ST519

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
13.00-24	12	TL	8.00	24.5	31	333	13.1	1278	50.3	300*450	44*65	2725*5600	6000*12300	40*10	25*5
13.00-24	14	TL	8.00	24.5	31	333	13.1	1278	50.3	525	76	6000	13200	10	5
13.00-24	16	TL	8.00	24.5	31	333	13.1	1278	50.3	400*600	58*87	3200*6500	7050*14300	40*10	25*5
14.00-24	12	TL	8.00	25.5	32	362	14.3	1348	53.1	325*425	47*62	3450*6300	7600*13900	40*10	25*5
14.00-24	16	TL	8.00	25.5	32	362	14.3	1348	53.1	375*550	54*80	3650*7300	8050*16100	40*10	25*5

OTR GRADER TIRE G2/L2-C/ST316

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
15.5-25	12	TL	12.00/1.3	25	32	394	15.5	1278	50.3	250	36	2650	5840	40	25
17.5-25	12	TL	14.00/1.5	25	32	445	17.5	1348	53.1	200	29	2900	6400	40	25
17.5-25	16	TL	14.00/1.5	25	32	445	17.5	1348	53.1	275	40	3350	7400	40	25
20.5-25	16	TL	17.00/2.0	26.5	33	521	20.5	1493	58.8	225	33	4000	8800	40	25
20.5-25	20	TL	17.00/2.0	26.5	33	521	20.5	1493	58.8	275	40	4500	9900	40	25



G3/L3



E4

OTR GRADER TIRE G3/L3

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
14.00-24TG	16	TL	10.00	25	32	375	14.8	1368	53.8	350	50	3650	8030	40	25
14.00-24TG	16	TL	10.00	25	32	375	14.8	1368	53.8	550	80	7300	16100	10	5

PORT USE TIRE E4

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
12.00-20	24	TT	8.50	45	57	315	12.4	1146	45.1	1000	145	9800	21600	50	30



L3/HT618



OTR RADIAL TIRE L3/HT618

Size	TT/TL	Load Index	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
17.5R25	TL	★★	14.00	26	33	445	17.5	1348	53.1	650	94	8500	18700	10	5
20.5R25	TL	★★	17.00	28.5	36	521	20.5	1493	58.8	650	94	11500	25400	10	5
23.5R25	TL	★★	19.50	32	40	597	23.5	1617	63.7	650	94	14500	32000	10	5
26.5R25	TL	★★	22.00	35	44	673	26.5	1750	68.9	650	94	18500	40800	10	5
29.5R25	TL	★★	25.00	38	48	749	29.5	1874	73.8	650	94	22400	49400	10	5

FORKLIFT TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
6.50-10NHS	10	TT	5.00	12	15	175	6.9	597	23.5	790	115	1400	3085	25	15
28X9-15/8.15-15	14	TT	7.00	16.5	21	221	8.7	706	27.8	970	140	3050	6720	25	15
7.00-12NHS	14	TT	5.00	14.5	18	190	7.5	676	26.6	1000	145	2590	5710	25	15
8.25-15NHS	16	TT	6.50	16	20	236	9.3	847	33.3	925	134	4050	8925	25	15
5.00-8NHS	10	TT	3.50	10	13	137	5.4	470	18.5	1000	145	1150	2535	25	15.5
6.00-9NHS	10	TT	4.00	12	15	160	6.3	540	21.3	860	125	1505	3315	25	15.5
6.50-10NHS	12	TT	5.00	12	15	175	6.9	590	23.2	1000	145	1895	4170	25	15.5
7.00-12NHS	12	TT	5.00	14.5	18	190	7.5	676	26.6	860	125	2375	5235	25	15.5
8.25-15NHS	14	TT	6.50	16	20	235	9.3	840	33.1	830	120	3775	8320	25	15.5
18x7-8NHS	14	TT	4.33	12	15	173	6.8	465	18.3	970	140	1505	3315	25	15.5
23x9-10NHS	16	TT	6.50	12	15	225	8.9	595	23.4	1030	150	2810	6195	25	15.5



F3



F-3



L4

INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
F3															
11L-16SL	12	TL	8.00	11	14	279	10.8	838	34.8	440	64	1250	2760	40	25
F-3															
11L-16	16	TL	8.00	12.7	16	279	11.00	838	31.82	525	76	1450	3195	40	25
L4															
11L-16SL	12	TL	8.00	16	20	279	12.1	838	38.0	440	64	1250	2760	40	25



NT198



R4

INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
							Section Width		Overall Diameter							
					(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
NT198																
16.9-28	16	TL	R4	15.00	24	30	429	16.9	1427	56.2	280	40	3700	8155	40	25
R4																
340/80R18		TL	R4	11.00	23.8	30	333	13.1	1008	39.7	320	46	2240	4940	50	30
500/75R24		TL	R4	16.00	27	34	495	19.5	1310	51.6	320	46	4125	9100	50	30



R4



L5

INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
R4															
10.5/80-18	10	TL	9.00	22	28	274	10.8	885	34.8	370	54	1950	4295	40	25
12.5/80-18	12	TL	9.00	27	34	308	12.1	965	38.0	370	54	2650	5840	40	25
12.5/80-18	14	TL	9.00	27	34	308	12.1	965	38.0	420	61	2850	6280	40	25
12.5/80-18	16	TL	9.00	27	34	308	12.1	965	38.0	490	71	3150	6945	40	25
L5															
11L-16	14	TL	8.00	35	44	280	11.0	845	33.3	470	68	1550	3415	40	25
12.5/80-18	14	TL	9.00	27	34	308	12.1	965	38.0	420	61	2850	6280	40	25
12.5/80-18	16	TL	9.00	27	34	308	12.1	965	38.0	490	71	3150	6945	40	25



R4

INDUSTRIAL TRACTORS

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
16.9-24	12	TL	15.00	27	34	429	16.9	1309	51.5	260	37	3250	7150	40	25
16.9-24	16	TL	15.00	27	34	429	16.9	1309	51.5	280	40	3600	7935	40	25
16.9-28	12	TL	15.00	33	35	429	16.9	1427	56.2	260	37	3550	7850	40	25
16.9-28	16	TL	15.00	33	30	429	16.9	1427	56.2	280	40	3700	8155	40	25
18.4-26	12	TL	16.00	28	35	467	18.4	1426	56.1	210	30	2900	6400	40	25
18.4-26	16	TL	16.00	28	35	467	18.4	1426	56.1	240	35	3200	7055	40	25
18.4-28	12	TL	16.00	39	49	467	18.4	1500	59.1	250	36	4000	8800	40	25
18.4-28	16	TL	16.00	39	49	467	18.4	1500	59.1	270	39	4250	9370	40	25



B/ST516

INDUSTRIAL TRACTORS R4

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
17.5L-24	12	TL	15.00	25	32	445	17.5	1241	48.9	190	28	1725	3800	40	25
19.5L-24	12	TL	17.00	26	33	495	19.5	1339	52.7	230	34	3450	7600	40	25
21L-24	12	TL	18.00	27	34	533	21.0	1378	54.3	220	32	3875	8550	40	25



A/ST515



C/ST517



D/L5

INDUSTRIAL TRACTORS R4

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
R4-A/ST515															
19.5L-24	12	TL	17.00	26	33	495	19.5	1339	52.7	230	34	3450	7600	40	25
19.5L-24	14	TL	17.00	26	33	495	19.5	1339	52.7	275	40	2800	6170	40	25
R4-C/ST517															
19.5L-24	12	TL	17.00	27.5	35	495	19.5	1339	52.7	230	34	3450	7600	40	25
19.5L-24	14	TL	17.00	26	33	495	19.5	1339	52.7	275	40	2800	6170	40	25
R4-D/L5															
19.5L-24	14	TL	17.00	38	48	495	19.5	1340	52.8	275	40	2800	6170	40	25
19.5L-24	16	TL	17.00	38	48	495	19.5	1340	52.8	310	45	3500	7715	40	25



SKS-1



SKS-2(L4)



SKS-4(KL4)



SKS-5(L5)

SKID STEER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter		Single		Single			
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
SKS-1															
10-16.5	10	TL	8.25	18	23	264	10.4	773	30.4	520	75	2135	4710	10	5
10-16.5	12	TL	8.25	18	23	264	10.4	773	30.4	620	90	2375	5240	10	5
12-16.5	12	TL	9.75	18	23	307	12.1	831	32.7	550	80	2865	6315	10	5
12-16.5	14	TL	9.75	18	23	307	12.1	831	32.7	620	90	3075	6780	10	5
14-17.5	14	TL	10.5	20	25	349	13.7	921	36.3	550	80	3875	8540	10	5
15-19.5	14	TL	11.75	20	25	389	15.3	1019	40.1	485	70	4565	10060	10	5
SKS-2(L4)															
10-16.5	10	TL	8.25	18	23	264	10.4	773	30.4	520	75	2135	4710	10	5
10-16.5	12	TL	8.25	18	23	264	10.4	773	30.4	620	90	2375	5240	10	5
12-16.5	12	TL	9.75	18	23	307	12.1	831	32.7	550	80	2865	6315	10	5
12-16.5	14	TL	9.75	18	23	307	12.1	831	32.7	620	90	3075	6780	10	5
14-17.5	14	TL	10.5	20	25	349	13.7	921	36.3	550	80	3875	8540	10	5
15-19.5	14	TL	11.75	20	25	389	15.3	1019	40.1	485	70	4565	10060	10	5
SKS-4(KL4)															
10-16.5	10	TL	8.25	18	23	264	10.4	773	30.4	520	75	2135	4710	10	5
10-16.5	12	TL	8.25	18	23	264	10.4	773	30.4	620	90	2375	5240	10	5
12-16.5	12	TL	9.75	18	23	307	12.1	831	32.7	550	80	2865	6315	10	5
12-16.5	14	TL	9.75	18	23	307	12.1	831	32.7	620	90	3075	6780	10	5
14-17.5	14	TL	10.5	20	25	349	13.7	921	36.3	550	80	3875	8540	10	5
15-19.5	14	TL	11.75	20	25	389	15.3	1019	40.1	485	70	4565	10060	10	5
SKS-5(L5)															
10-16.5	12	TL	8.25	34	43	264	10.4	805	31.7	620	90	2375	5240	10	5
12-16.5	14	TL	9.75	35	44	312	12.3	835	32.9	620	90	3075	6780	10	5
14-17.5	14	TL	10.50	35	44	349	13.7	921	36.3	550	80	3875	8540	10	5



F2/3RIB

F2/4RIB

F2

T239

FARM TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
F2/3RIB															
7.5L-15	8	TT /TL	6.00	17	21	208	8.2	745	29.3	370	53	840	1850	40	25
9.5L-15	8	TT /TL	7.00	20	25	240	9.4	780	30.7	330	48	850	1870	40	25
11L-15	8	TT /TL	8.00	19	24	280	11.0	810	31.9	300	44	950	2090	40	25
6.00-16SL	6	TT /TL	4.00	17	21	159	6.3	739	29.1	360	52	515	6005	40	25
7.50-16SL	8	TT /TL	5.50	20	25	203	8.0	808	31.8	385	56	775	1705	40	25
F2/4RIB															
10.00-16SL	10	TT /TL	8.00	25	32	274	10.8	894	35.2	300	44	1120	2480	40	25
11.00-16SL	12	TT /TL	10.00	24	30	315	12.4	967	38.1	410	60	1550	3420	40	25
F2															
7.50-16	14	TL	5.50	14	18	203	8.0	808	31.8	470	68	980	2160	40	25
10.00-16	14	TL	8.00	20.6	26	274	10.8	894	35.2	360	52	1160	2555	40	25
11.00-16	14	TL	10.00	23	29	315	12.4	967	38.1	440	64	1600	3525	40	25

TRACTION TYPE TRAILER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
T239															
9.00-16	16	TT /TL	6.00F	16.5	21	245	9.6	890	35.0	500	72	1833	4040	30	20



I1

IMP-01

R1

IMPLEMENT TIRE I1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
9.5L-15SL	8	TL	7.00	7.5	9	241	9.5	767	30.2	300	53	1120	2470	40	25
9.5L-15SL	12	TL	7.00	7.5	9	241	9.5	767	30.2	440	64	1450	3200	40	25
11L-15SL	8	TL	8.00	7.5	9	279	11.0	777	30.6	250	44	1150	2540	40	25
11L-15SL	12	TL	8.00	7.5	9	279	11.0	777	30.6	360	52	1450	3200	40	25
12.5L-15SL	12	TL	10.00	7.5	9	318	12.5	823	32.4	360	52	1750	3860	40	25

IMPLEMENT&TRAILER TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
10.0/75-15.3	10	TL	IMP-01	9.00	9	11	264	10.4	760	29.9	390	57	1550	3415	40	25
10.0/75-15.3	12	TL	IMP-01	9.00	9	11	264	10.4	760	29.9	470	68	1550	3415	40	25
11.5/80-15.3	12	TL	IMP-01	9.00	10	13	290	11.4	845	33.3	410	59	2180	4805	40	25
11.5/80-15.3	14	TL	IMP-01	9.00	10	13	290	11.4	845	33.3	475	69	2430	5355	40	25
12.5/80-15.3	14	TL	IMP-01	9.00	10.5	13	307	12.1	889	35.0	430	62	2650	5840	40	25
12.5/80-15.3	16	TL	IMP-01	9.00	10.5	13	307	12.1	889	35.0	490	71	2820	6215	40	25

MPT TIRE R1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
10.0/75-15.3	8	TL	9.00	25	32	264	10.4	760	29.9	310	44	950	2100	40	25
10.0/75-15.3	10	TL	9.00	25	32	264	10.4	760	29.9	390	56	1090	2400	40	25
10.0/75-15.3	12	TL	9.00	25	32	264	10.4	760	29.9	470	68	1180	2600	40	25
11.5/80-15.3	8	TL	9.00	25	32	290	11.4	845	33.3	270	39	1180	2600	40	25
11.5/80-15.3	12	TL	9.00	25	32	290	11.4	845	33.3	340	49	1360	3000	40	25
11.5/80-15.3	14	TL	9.00	25	32	290	11.4	845	33.3	475	69	1700	3745	40	25



AGRICULTURE TIRE R1-1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
5.00-15	6	TL	4.00	15	19	130	5.1	640	25.2	350	50	455	1005	40	25
7.50-16	6	TT /TL	5.50	26	33	205	8.1	810	31.9	210	30	650	1430	40	25

AGRICULTURE TIRE R1-2

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
12.4-24	8	TT /TL	11.00	36	45	315	12.4	1159	45.6	220	32	1285	2830	40	25
12.4-24	12	TT /TL	11.00	36	45	315	12.4	1159	45.6	330	48	1600	3520	40	25
13.6-24	8	TT /TL	12.00	36	45	345	13.6	1210	47.6	190	28	1400	3080	40	25
13.6-24	12	TT /TL	12.00	36	45	345	13.6	1210	47.6	250	36	1790	3945	40	25
14.9-24	8	TT /TL	13.00	36	45	378	14.9	1265	49.8	180	26	1600	3520	40	25
14.9-24	12	TT /TL	13.00	36	45	378	14.9	1265	49.8	260	38	2000	4400	40	25
14.9-28	8	TT /TL	13.00	36	45	378	14.9	1367	53.8	180	26	1700	3740	40	25
14.9-28	12	TT /TL	13.00	36	45	378	14.9	1367	53.8	250	36	2120	4670	40	25

AGRICULTURE TIRE R1-3

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
23.1-26	12	TT /TL	20.00	40	50	587	23.1	1605	63.2	165/170	24	3250	7150	40	25
16.9-30	10	TT /TL	15.00	37	47	429	16.9	1485	58.5	165	24	2000	4400	40	25
18.4-30	10	TT /TL	16.00	37.5	47	467	18.4	1552	61.1	180	26	2500	5510	40	25
18.4-30	12	TT /TL	16.00	37.5	47	467	18.4	1552	61.1	220	32	2900	6400	40	25
18.4-34	10	TT /TL	16.00	37.5	47	467	18.4	1654	65.1	180	26	2725	6000	40	25
18.4-34	12	TT /TL	16.00	37.5	47	467	18.4	1654	65.1	220	32	3000	6600	40	25
15.5-38	8	TT /TL	14.00	37.5	47	394	15.5	1569	61.8	180	26	1850	4075	40	25
15.5-38	10	TT /TL	14.00	37.5	47	394	15.5	1569	61.8	220	32	2100	4630	40	25
18.4-38	10	TT /TL	16.00	37.5	47	467	18.4	1802	70.9	180	26	2900	6400	40	25
18.4-38	12	TT /TL	16.00	37.5	47	467	18.4	1802	70.9	220	32	3250	7150	40	25



AGRICULTURE TIRES R1W

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
							Section Width		Overall Diameter							
					(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
11.2-24	12	TT	R1W	10.00	40	50	284	11.2	1103	43.4	330	48	1450	3195	40	25
12.4-24	12	TT	R1W	11.00	40	50	315	12.4	1159	45.62	330	48	1600	3520	40	25
13.6-24	12	TT	R1W	12.00	43	54	345	13.6	1210	47.6	250	36	1790	3945	40	25
14.9-24	12	TT	R1W	13.00	45	57	378	14.9	1265	49.8	260	38	2000	4400	40	25
16.9-30	12	TT	R1W	15.00	45	57	429	16.9	1485	58.48	230	34	2500	5520	40	25
14.9-38	12	TT	R1W	13.00	43	54	378	14.9	1621	63.8	250	36	2130	4695	40	25
18.4-30	12	TT	R1W	16.00	45	57	467	18.4	1552	61.1	220	32	2900	6400	40	25
18.4-34	12	TT	R1W	16.00	45	57	467	18.4	1654	65.1	220	32	3000	6600	40	25
18.4-38	12	TT	R1W	16.00	45	57	467	18.4	1802	70.9	220	32	3250	7150	40	25
15.5-38	12	TT	R1W	14.00	40	50	394	15.5	1569	61.8	240	35	2350	5180	40	25
30.5L-32	18	TL	R1W	27.00	52	65	775	30.5	1819	71.6	190	28	5250	11575	40	25
14.9-28	12	TT	R1W	13.00	45	57	378	14.9	1367	53.82	250	36	2120	4670	40	25
16.9-28	12	TT	R1W	15.00	45	57	429	16.9	1435	56.48	300	44	3875	8540	40	25
16.9-38	14	TT	R1W	15.00	45	56	429	16.9	1689	66.5	250	36	2750	6060	40	25
18.4-26	12	TT	R1W	16.00	45	57	467	18.4	1450	57.10	220	32	2650	5840	40	25
20.8-34	14	TT	R1W	18.00	48	61	528	20.8	1732	68.2	220	32	3725	8210	40	25
20.8-38	14	TT	R1W	18.00	48	60	528	20.8	1834	72.20	220	32	3875	8550	40	25
16.9-24	12	TT	R1W	15.00	45	57	429	16.90	1333	52.48	230	34	2300	5080	40	25
16.9-34	12	TT	R1W	15.00	45	57	429	16.90	1587	62.48	230	34	2720	5995	40	25
24.5-32	16	TL	R1W	21.00	50	63	622	24.50	1803	71.00	210	30	4500	9900	40	25
18.4-42	14	TL	R1W	16.00	45	57	467	18.40	1857	73.10	250	36	3650	8050	40	25
18.4-46	16	TL	R1W	16.00	45	57	467	18.40	1958	77.10	320	46	4475	9865	40	25



R2



R1W/HT616

AGRICULTURE TIRE R2

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
						Section Width		Overall Diameter							
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
12.4-24	10	TT	W11	60	75	315	12.4	1192	46.9	260	38	1450	3195	40	25
14.9-24	10	TT	W13	69	87	378	14.9	1305	51.4	220	32	1800	3960	40	25
14.9-28	10	TT	W13	69	87	378	14.9	1406	55.4	220	32	1900	4180	40	25
23.1-26	12	TT	DW20	80	100	587	23.1	1662	65.4	170	25	3250	7150	40	25
18.4-30	10	TT	W16L	90	113	467	18.4	1599	63.0	180	26	2500	5520	40	25
18.4-30	12	TT	W16L	90	113	467	18.4	1599	63.0	220	32	2900	6400	40	25
18.4-34	10	TT	W16L	90	113	467	18.4	1701	67.0	180	26	2725	6000	40	25
18.4-34	12	TT	W16L	90	113	467	18.4	1701	67.0	220	32	3000	6600	40	25
18.4-38	10	TT	W16L	90	113	467	18.4	1802	70.9	180	26	2900	6400	40	25
18.4-38	12	TT	W16L	90	113	467	18.4	1802	70.9	220	32	3250	7150	40	25

AGRICULTURE RADIAL TIRES R1W

Size	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Load Index	Pressure		Max. Load		Speed	
						Section Width		Overall Diameter								
				(mm)	(32nd)	(mm)	inch	(mm)	inch		(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
340/85R28	TL	R1W	11.00	44	55	343	13.5	1289	50.7	125A8	160	23	1750	3850	40	25
380/85R30	TL	R1W	12.00	45	57	380	14.9	1408	55.4	135A8	160	23	2180	4800	40	25
420/85R28	TL	R1W	13.00	48	60	418	16.5	1425	56.0	139A8	160	23	2430	5360	40	25
420/85R30	TL	R1W	13.00	48	60	418	16.5	1476	58.1	140A8	160	23	2500	5510	40	25
540/65R28	TL	R1W	18.00	46	58	550	21.5	1413	55.6	142A8	160	23	2650	5840	40	25
540/65R30	TL	R1W	18.00	46	58	550	21.5	1464	57.6	143A8	160	23	2725	6005	40	25
460/85R30	TL	R1W	14.00	48	60	455	18.4	1544	60.8	145A8	160	23	2900	6395	40	25
460/85R34	TL	R1W	14.00	48	60	455	18.4	1646	64.8	147A8	160	23	3075	6780	40	25
460/85R38	TL	R1W	14.00	48	60	455	18.4	1747	68.8	149A8	160	23	3250	7165	40	25
380/85R28	TL	R1W	12.00	45	57	380	14.9	1357	53.4	133A8	160	23	2060	4540	40	25
400/75R38	TL	R1W	13.00	42	53	404	15.5	1565	61.6	138A8	160	23	2360	5200	40	25



R1W/HT616

AGRICULTURE RADIAL TIRES R1W

Size	TT/TL	PATTERN	Rim	New tire inflated dimensions				Pressure		Max. Load		Speed
				Section Width		Overall Diameter						
				(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	
280/85R20	TL	R1W	W10	283	11.1	984	38.7	160	23	1120	2470	A8/B
280/85R24	TL	R1W	W10	282	11.1	1086	42.8	160	23	1215	2680	A8/B
300/95R46	TL	R1W	W9	305	12.0	1717	67.6	400	58	3150	6945	A8/B
320/85R24	TL	R1W	W10	319	12.6	1154	45.4	160	23	1500	3310	A8/B
320/85R28	TL	R1W	W10	319	12.6	1255	49.4	160	23	1600	3530	A8/B
320/85R36	TL	R1W	W11	328	12.9	1455	57.3	160	23	1800	3970	A8/B
320/90R46	TL	R1W	W10	312	12.3	1744	68.7	400	58	3150	6945	A8/B
340/85R24	TL	R1W	W11	343	13.5	1188	46.8	160	23	1500	3310	A8/B
380/85R24	TL	R1W	W12	380	15.0	1256	49.4	160	23	1950	4300	A8/B
380/85R28	TL	R1W	W12	380	15.0	1357	53.4	160	23	2060	4540	A8/B
380/80R38	TL	R1W	W12	380	15.0	1573	61.9	160	23	2120	4670	A8/B
380/90R46	TL	R1W	W12	380	15.0	1852	72.9	240	35	3250	7165	A8/B
380/70R24	TL	R1W	W12	380	15.0	1190	46.9	160	23	1650	3640	A8/D
420/70R24	TL	R1W	W13	418	16.5	1248	49.1	160	23	1900	4190	A8/B
420/70R28	TL	R1W	W13	418	16.5	1349	53.1	160	23	2060	4540	A8/D
420/85R34	TL	R1W	W13	418	16.5	1578	62.1	160	23	2650	5840	A8/B
480/70R24	TL	R1W	W15L	479	18.9	1316	51.8	400	58	4750	10470	A8/B
480/70R28	TL	R1W	W15L	479	18.9	1421	55.9	160	23	2500	5510	A8/D
480/70R30	TL	R1W	W15L	479	18.9	1478	58.2	160	23	2575	5680	A8/D
480/70R34	TL	R1W	W15L	479	18.9	1580	62.2	350	51	3875	8540	A8/D
480/80R46	TL	R1W	W15L	479	18.9	1936	76.2	240	35	4250	9370	A8/B
520/70R34	TL	R1W	W16L	516	20.3	1640	64.6	160	23	3150	6945	A8/D
520/70R38	TL	R1W	W16L	516	20.3	1749	68.9	160	23	3350	7385	A8/D
580/70R38	TL	R1W	W18L	577	22.7	1827	71.9	160	23	3875	8540	A8/D
520/85R38	TL	R1W	W18L	560	22.0	1857	73.1	160	23	3875	8540	A8/B
520/85R42	TL	R1W	DW18L	560	22.0	1969	77.5	160	23	4125	9090	A8/B
600/65R28	TL	R1W	W18L	591	23.3	1491	58.7	160	23	3075	6780	A8/B
620/70R42	TL	R1W	DW20B	625	24.6	1935	76.2	160	23	4500	9920	A8/D
650/65R42	TL	R1W	DW20A	645	25.4	1913	75.3	240	35	5150	11350	A8/D
650/65R38	TL	R1W	DW20A	645	25.4	1811	71.3	240	35	4875	10750	A8/B
710/70R42	TL	R1W	DW23A	716	28.2	2061	81.1	160	23	5600	12350	A8/D
710/70R38	TL	R1W	W23	716	28.2	1959	77.1	160	23	5300	11680	A8/B
800/65R32	TL	R1W	DW27B	798	31.4	1853	73.0	360	52	8250	18190	A8/B
IF600/70R30	TL	R1W	DW18L	591	23.3	1602	63.1	240	35	5150	11350	A8/D
VF380/90R46	TL	R1W	DW12	185	7.3	3855	151.8	440	64	6500	14330	D



R1

Irrigation R1

Non-Direction R1

AGRICULTURE TIRE R1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
13.6-38	8	TT	DW12A	34	43	345	13.6	1565	61.6	190	28	1700	3740	40	25
13.6-38	12	TT	DW12A	34	43	345	13.6	1565	61.6	290	42	2180	4800	40	25

IRRIGATION TIRE R1

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
11.2-24	6	TT	10.00	25	32	284	11.2	1103	43.4	180	26	950	2090	40	25
11.2-24	8	TT	10.00	25	32	284	11.2	1103	43.4	250	36	1150	2540	40	25
11.2-38	6	TT	10.00	25	32	284	11.2	1459	57.4	180	26	1150	2530	40	25
11.2-38	8	TT	10.00	25	32	284	11.2	1459	57.4	220	32	1300	2865	40	25
14.9-24	6	TT	13.00	25	32	378	14.9	1265	49.8	180	26	1600	3520	40	25
14.9-24	8	TT	13.00	25	32	378	14.9	1265	49.8	230	34	1850	4080	40	25

IRRIGATION TIRE R1 NON-DIRECTION

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
11.2-24	6	TT/TL	10.00	25	32	284	11.2	1103	43.4	180	26	950	2090	40	25
11.2-24	8	TT/TL	10.00	25	32	284	11.2	1103	43.4	250	36	1150	2540	40	25
11.2-38	6	TT/TL	10.00	25	32	284	11.2	1459	57.4	180	26	1150	2530	40	25
11.2-38	8	TT/TL	10.00	25	32	284	11.2	1459	57.4	220	32	1300	2865	40	25
14.9-24	6	TT/TL	13.00	25	32	378	14.9	1265	49.8	180	26	1600	3520	40	25
14.9-24	8	TT/TL	13.00	25	32	378	14.9	1265	49.8	230	34	1850	4080	40	25



L-6T+

L-6T+

MUD'R TP



L-6T+EXT

L-6S++EXT

RUBBER MINE TIRE

Size	P.R.	TT/TL	Rim	Tread	New tire inflated dimensions				Pressure		Max. Load		Speed	
					Section Width	Overall Diameter			(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
675*212-15	16	TL	6.00	L-6T+	209	8.2	689	27.1	415	60	2250	4960	10	5
850*350-16.5	42	TL	11.50	L-6T+	368	14.5	844	33.2	1170	170	4850	10690	10	5
850*350-15	42	TL	11.50	L-6T+	368	14.5	844	33.2	1170	170	4850	10690	10	5
875*375-15.1F	42	TL	11.50	L-6T+	375	14.8	859	33.8	1170	170	4850	10690	10	5
875*375-15.1F	48	TL	11.50	MUD'R TP	375	14.8	859	33.8	1310	190	5250	11575	10	5
875*375-16.5F	42	TL	11.50	L-6T+	375	14.8	859	33.8	1170	170	4850	10690	10	5
1385*490-650	60	TL	14.00	L-6S++ EXT	445	17.5	1400	55.1	575	83	8250	18200	10	5
1558*508-27.1	30	TL	11.25	L-6T+R EXT	432	17.0	1548	60.9	780	113	11800	26010	10	5
1000*500-16	48	TL	16.00	L-6T+ EXT	485	19.1	980	38.6	1200	174	5000	11020	10	5
1000*450-15.1F	48	TL	14.00	L-6T+ EXT	437	17.2	980	38.6	1150	167	4750	10470	10	5
1375*355-27.3	48	TL	10.00	L-6T+	375	14.8	1370	53.9	1300	188	13500	29760	10	5
1150x325-20	42	TL	8.50	L-6T+ EXT	315	12.4	1175	46.3	1300	188	12500	27555	10	5
1150x325-21	42	TL	8.50	L-6T+ EXT	315	12.4	1175	46.3	1300	188	12500	27555	10	5



FORESTRY TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
16.9-30	10	TT/TL	W15L	48	60	210	8.3	1510	59.4	210	30.5	2575	5680	30	18.6
16.9-30	16	TT/TL	W15L	48	60	210	8.3	1510	59.4	300	43.5	3210	7080	30	18.6
18.4-26	10	TT/TL	DW16A	50	63	465	18.3	1475	58.1	170	24.7	2575	5680	30	18.6
18.4-26	16	TT/TL	DW16A	50	63	465	18.3	1475	58.1	280	40.6	3500	7720	30	18.6
18.4-30	10	TT/TL	DW16A	50	63	465	18.3	1575	62.0	170	24.7	2725	6010	30	18.6
18.4-30	16	TT/TL	DW16A	50	63	465	18.3	1575	62.0	280	40.6	3600	7940	30	18.6
18.4-34	12	TT/TL	DW16A	50	63	465	18.3	1680	66.1	210	30.5	3250	7165	30	18.6
18.4-34	16	TT/TL	DW16A	50	63	465	18.3	1680	66.1	280	40.6	3700	8160	30	18.6
23.1-26	14	TT/TL	DW20A	53	66	590	23.2	1630	64.2	210	30.5	4125	9090	30	18.6
23.1-26	16	TT/TL	DW20A	53	66	590	23.2	1630	64.2	240	34.8	4450	9810	30	18.6
24.5-32	16	TT/TL	DH21	55	69	625	24.6	1830	72.0	210	30.5	5000	11020	30	18.6
24.5-32	20	TT/TL	DH21	55	69	625	24.6	1830	72.0	280	40.6	5800	12790	30	18.6
DH35.5L-32	20	TT/TL	DH32	58	73	905	35.6	2004	78.9	240	34.8	6530	14400	30	18.6
DH35.5L-32	26	TT/TL	DH32	58	73	905	35.6	2004	78.9	280	40.6	8750	19290	30	18.6
73x44.00-32	16	TL	DH36	67	84	1153	45.4	1870	73.6	280	40.6	6900	15210	30	18.6
73x44.00-32	20	TL	DH36	67	84	1153	45.4	1870	73.6	340	49.3	8000	17640	30	18.6
30.5L-32	26	TL	27.00	55	69	775	30.50	1847	72.70	275	40	7100	15700	30	20
30.5L-32	26	TL	27.00	55	69	775	30.50	1847	72.70	310	45	10000	22000	10	5
28L-26	26	TL	25.00	56	71	714	28.10	1644	64.72	340	50	6050	13330	30	20
28L-26	26	TL	25.00	56	71	714	28.10	1644	64.72	380	55	8500	18735	10	5



FORESTRY TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
500/60-26.5	20	TT/TL	AG 16.00	53	66	485	19.1	1265	49.8	500	72.5	5150	11350	40	24.9
600/50-22.5	20	TT/TL	AG 20.00	42	53	600	23.6	1170	46.1	550	79.8	4375	9645	40	24.9
600/55-26.5	20	TT/TL	AG 20.00	48	60	601	23.7	1340	52.8	550	79.8	5150	11350	40	24.9
650/45-22.5	20	TT/TL	AG 20.00	45	56	635	25.0	1153	45.4	500	72.5	3750	8270	40	24.9
700/45-22.5	20	TT/TL	AG 24.00	42	53	710	28.0	1170	46.1	550	79.8	4625	10200	40	24.9
700/50-26.5	20	TT/TL	AG 24.00	48	60	710	28.0	1340	52.8	550	79.8	5600	12350	40	24.9
710/40-22.5	20	TT/TL	AG 24.00	42	53	710	28.0	1170	46.1	550	79.8	4625	10200	40	24.9
710/40-24.5	20	TT/TL	AG 24.00	48	60	710	28.0	1230	48.4	550	79.8	4875	10750	40	24.9
710/45-26.5	20	TT/TL	AG 24.00	48	60	710	28.0	1340	52.8	550	79.8	5600	12350	40	24.9
710/55-28.5	24	TT/TL	AG 24.00	49	61	710	28.0	1525	60.0	600	87.0	8000	17640	40	24.9
750/55-26.5	24	TT/TL	AG 24.00	49	61	750	29.5	1485	58.5	600	87.0	8500	18740	40	24.9
780/50-28.5	24	TT/TL	AG 26.00	49	61	780	30.7	1525	60.0	600	87.0	8500	18740	40	24.9
800/40-26.5	20	TT/TL	AG 28.00	48	60	800	31.5	1340	52.8	550	79.8	6000	13230	40	24.9



TRC02

FLOTATION TIRE TRC02

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load		Speed	
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)	Km/h	mph
400/60-15.5	16	TL	13.00	18	23	404	16	874	34.4	400	58	3250	7165	40	25



T322

T324

T325

HT326

LPT BIAS TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
7-14.5 ST	12	TL	T322	6.00	6	8	194	7.6	680	26.8	690	100	1059	2335
8-14.5 ST	14	TL	T322	6.00	6	8	203	8.0	707	27.8	790	115	1405	3100

MOBILE HOME TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
8-14.5	14	TL	T322	6.00	6	8	194	7.6	680	26.8	790	115	1405	3100
8-14.5	14	TL	T322	6.00	6	8	194	7.6	680	26.8	790	115	1585	3500
8-14.5	16	TL	T322	6.00	6	8	194	7.6	680	26.8	790	115	1585	3500
8-14.5	14	TL	T322	6.00	6	8	203	8.0	707	27.8	790	115	1405	3100
9-14.5	14	TL	T324	7.00	9	11	241	9.5	711	28.0	790	115	1590	3500
215/60D14.5	14	TL	T325	6.00	6	8	196	7.7	628	24.7	760	110	1405	3100
235/60D14.5	14	TL	T325	7.00	7	9	230	9.1	673	26.5	760	110	1590	3500

SPECIAL TRAILER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
				(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
ST175/80D13	6	TL	5.00	6.5	8	177	7.0	610	24.0	350/*350	50/*50	545/*615	1200/*1360
ST205/65D14	6	TL	5.50	7.5	9	192	7.6	620	24.4	350/*350	50/*50	800/*710	1760/*1570
ST205/75D14	6	TL	5.50	8	10	203	8.0	664	26.1	350/*350	50/*50	710/*800	1570/*1760
ST205/75D15	6	TL	5.50	8	10	203	8.0	689	27.1	350/*350	50/*50	730/*825	1610/*1820
ST225/75D15	8	TL	6.00	8	10	223	8.8	719	28.3	450/*450	65/*65	1000/*1150	2200/*2540



HT327

HT328

HT329

HT330

SPECIAL TRAILER TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
16.5x6.5-8	4	TL	HT327	5.375	5.5	7	166	6.5	418	16.5	310	45	280	620
16.5x6.5-8	6	TL		5.375	5.5	7	166	6.5	418	16.5	480	70	320	620
20.5x8.0-10	4	TL		6.00	7	9	203	8.0	518	20.4	240	35	412	910
20.5x8.0-10	6	TL		6.00	7	9	203	8.0	518	20.4	340	50	501	1105
20.5x8.0-10	8	TL		6.00	7	9	203	8.0	518	20.4	480	70	603	1330
20.5x8.0-10	10	TL		6.00	7	9	203	8.0	518	20.4	620	90	696	1535
20.5x8.0-10	12	TL		6.00	7	9	203	8.0	518	20.4	650	95	787	1735
22.5x8.0-12	12	TL		6.00	7.5	9	222	8.7	572	22.5	755	110	895	1980
16.5x6.5-8	4	TL	HT328	5.375	7	9	166	6.5	418	16.5	310	45	280	620
16.5x6.5-8	6	TL		5.375	7	9	166	6.5	418	16.5	480	70	320	705
18.5x8.5-8	4	TL		7.00	7	9	213	8.4	462	18.2	240	35	349	770
18.5x8.5-8	6	TL		7.00	7	9	213	8.4	462	18.2	340	50	500	1100
20.5x8.0-10	4	TL		6.00	7	9	203	8.0	518	20.4	240	35	412	910
20.5x8.0-10	6	TL		6.00	7	9	203	8.0	518	20.4	340	50	501	1105
20.5x8.0-10	8	TL		6.00	7	9	203	8.0	518	20.4	480	70	603	1330
20.5x8.0-10	10	TL		6.00	7	9	203	8.0	518	20.4	620	90	696	1535
20.5x8.0-10	12	TL		6.00	7	9	203	8.0	518	20.4	650	95	787	1735
4.80-8	4	TL	HT329	3.75	5.5	7	121	4.8	423	16.7	410	60	267	590
4.80-8	6	TL		3.75	5.5	7	121	4.8	423	16.7	620	90	345	760
5.70-8	4	TL		4.50	6	8	146	5.7	469	18.5	340	50	325	715
5.70-8	6	TL		4.50	6	8	146	5.7	469	18.5	520	75	412	910
5.70-8	8	TL		4.50	6	8	146	5.7	469	18.5	690	100	487	1070
5.70-8	8	TL		4.50	6	8	146	5.7	469	18.5	690	100	490	1075
4.80-12	4	TL		3.75	5.5	7	121	4.8	524	20.6	410	60	267	590
4.80-12	6	TL		3.75	5.5	7	121	4.8	524	20.6	620	90	450	990
5.30-12	4	TL		4.25	6	8	135	5.3	548	21.6	380	55	387	855
5.30-12	6	TL		4.25	6	8	135	5.3	548	21.6	550	80	475	1050

GOLF CART TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
18x8.5-8	4	TL	HT328	7	6	8	213	8.4	445	17.5	150	22	370	815



T236

T237

T238

E116

TRAILER TIRE

Size	P.R.	TT/TL	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
						Section Width		Overall Diameter					
				(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
T236													
ST205/90D15	10	TL	5J	9.5	12	200	7.9	750	29.5	550*550	80*80	1320/1150	2910/2540
ST225/90D16	10	TL	6J	9.5	12	215	8.5	805	31.7	520*520	75*75	1560/3440	1370/3020
T237													
7.00-15	8	TL	5.50F	11	14	200	7.9	750	29.5	410/*410	60/*60	825/*925	1820/*2040
7.00-15	10	TL	5.50F	11	14	200	7.9	750	29.5	520/*520	75/*75	925/*1060	2040/*2335
7.50-16	10	TL	6.00G	12	15	215	8.5	805	31.7	520/*520	75/*75	1120/*1250	2470/*2755
7.50-16	12	TL	6.00G	12	15	215	8.5	805	31.7	630/*630	91/*91	1400/*1250	3085/*2755
T238													
ST205/90D15	10	TL	5J	9.5	12	200	7.9	750	29.5	550*550	80*80	1320/1150	2910/2540
ST225/90D16	10	TL	6J	9.5	12	215	8.5	805	31.7	520*520	75*75	1560/3440	1370/3020
E116													
7.50-16	10	TL	6.00G	11	14	215	8.5	805	31.7	520/*520	75/*75	1120/*1250	2470/*2755
7.50-16	12	TL	6.00G	11	14	215	8.5	805	31.7	630/*630	91/*91	1400/*1250	3085/*2755
ST225/90D16	10	TL	6J	9.5	12	215	8.5	805	31.7	520*520	75*75	1560/3440	1370/3020



BIAS TRUCK TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
							Section Width		Overall Diameter					
					(mm)	(32nd)	(mm)	inch	(mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
NT161														
N78-15LT	6	TL	T161	7.00	22	28	230	9.1	785	30.9	310	45	872	1920
P78-16LT	6	TL	T161	6.50	23	29	219	8.6	830	32.7	310	45	990	2180
T332														
7.50-17	10	TL	T332	6.00	10.5	13	215	8.5	859	33.8	550/*620	80/*90	1260/*1440	2780/*3170
T311														
10.00-20	14	TT	T311	7.50	11.5	14	278	10.9	1054	41.5	620/*690	90/*100	2430/*2800	5355/*6175



T321

TRAILER TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth		New tire inflated dimensions				Pressure		Max. Load	
					(mm)	(32nd)	Section Width (mm)	inch	Overall Diameter (mm)	inch	(kPa)	(psi)	(kg)	(Lbs)
10.00-20	12	TT	T321	7.5	11.5	14	278	10.9	1054	41.5	520/*590	75/*85	2180/*2500	4805/*5510
10.00-20	14	TT	T321	7.5	11.5	14	278	10.9	1054	41.5	620/*690	90/*100	2430/*2800	5355/*6175
11-22.5	12	TL	T321	8.25	11.5	14	279	11.0	1054	41.5	520/*590	75/*85	2180/*2500	4805/*5510
11-22.5	14	TL	T321	8.25	11.5	14	279	11.0	1054	41.5	620/*690	90/*100	2430/*2800	5840/*6610



K72



K-305

BIAS TRUCK TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth	New tire inflated dimensions		Pressure		Max. Load	
						Section Width	Overall Diameter				
						(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)
7.00-15	10	TL	K72	5.50F	11	200	750	520/*520	75/*75	925/*1060	2040/*2335
7.50-16	10	TL	K72	6.00G	12	215	805	520/*520	75/*75	1120/*1250	2470/*2755
8.25-20	10	TT	K72	6.50	12	236	974	530/*600	77/*87	1600/*1850	3520/*4075
9.00-20	10	TT	K72	7.00	12	259	1018	490/*560	71/*81	1850/*2120	4075/*4670
10.00-20	12	TT	K72	7.50	13.5	278	1055	520/*590	75/*85	2180/*2500	4805/*5510
8.25-20	10	TT	K-305	6.50	19	236	974	530/*600	77/*87	1600/*1850	3520/*4075
9.00-20	10	TT	K-305	7.00	21	259	1018	490/*560	71/*81	1850/*2120	4075/*4670
10.00-20	12	TT	K-305	7.50	20.5	278	1055	520/*590	75/*85	2180/*2500	4805/*5510



KS601



KS602

MINING TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth	New tire inflated dimensions		Pressure		Max. Load	
						Section Width	Overall Diameter				
						(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)
7.50-16	14	TT	KS601	6.00G	22	215	805	730/*730	106/*106	1320/*1500	2910/*3300
10.00-20	16	TT	KS601	7.50	25	278	1073	740/*810	105/*115	2650/*3000	5840/*6610
8.25-16	16	TT	KS602	6.50H	14	235	867	730/*730	106/*106	1600/*1800	3520/*3960



L-5S
L-5SA
L-5SL

UNDERGROUND MINING TIRES

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth	New tire inflated dimensions		Pressure	Max. Load
						Section Width	Overall Diameter		
						(mm)	(mm)	(kPa)	(kg)
29.5-29	40	TL	L-5S	25.00/3.5	110	750	2025	625	23600
29.5-25	34	TL	L-5S	25.00/3.5	110	750	1920	525	19800
26.5-25	36	TL	L-5S/L-5SL	22.00/3.0	100/80	675	1800	625	18500
18.00-25	32	TL	L-5S	13.00/2.5	85	526	1673	750	15000
17.5-25	24	TT/TL	L-5S	14.00/1.5	82	445	1400	675	9000
17.5-25	20	TT/TL	L-5S/L-5SL/L-5SA	14.00/1.5	82/63.5/45.5	445	1400	575	8250
14.00-24	28	TT	L-5S/L-5SL	10	77/63.5	386/375	1417/1420	1000/925	13500/10000
12.00-24	24	TT	L-5S/L-5SL	8.5	55/47	333	1300	1000	10250
12.00-20	28	TT	L-5S	8.5	67	340	1173	1030	8620
12.00-20	20	TT	L-5SA	8.5	57	315	1145	900	6325
10.00-20	18	TT	L-5S	7.5	58	300	1097	1000	7255
8.25-15	24	TT	L-5S	6.5	52	260	864	1030	6070

BIAS TRUCK TIRE

Size	P.R.	TT/TL	PATTERN	Rim	Tread Depth	New tire inflated dimensions		Pressure		Max. Load	
						Section Width	Overall Diameter				
						(mm)	(mm)	(kPa)	(psi)	(kg)	(Lbs)
6.00-13	8	TT	HIW/LUG	4.50B	9	170	655	420/*420	61/*61	580/*650	1280/*1430
6.00-14	8	TT	HIW/LUG	41/2J	9	170	680	420/*420	61/*61	600/*690	1320/*1520
6.00-14	10	TT	HIW	41/2J	9	170	680	530/*530	77/*77	710/*800	1565/*1760
6.00-14	10	TT	HIW	41/2J	15.5	170	680	530/*530	77/*77	710/*800	1565/*1760
6.00-15	10	TT	HIW	4.50E	15	170	705	530/*530	77/*77	825/*930	1820/*2340
6.50-14	8	TT	HIW	41/2J	9	180	705	420/*420	61/*61	690/*785	1520/*1730
6.50-15	10	TT	HIW	4.50E	10	180	730	530/*530	77/*77	840/*950	1850/*2090
6.50-16	12	TT	HIW/LUG	5.50F	11	185	750	630/*630	91/*91	925/*1060	2040/*2335
7.00-15	12	TT	HIW	5.50F	9.5	200	750	630/*630	91/*91	1030/*1150	2265/*2530
7.00-16	14	TT	HIW/LUG	5.50F	11	200	775	730/*730	106/*106	1180/*1320	2600/*2910
7.50-16	14	TT	HIW/LUG	6.00G	11	215	805	730/*730	106/*106	1320/*1500	2910/*3300
8.25-16	14	TT	HIW/LUG	6.50H	13	235	855	630/*630	91/*91	1500/*1700	3305/*3745
7.50-20	14	TT	HIW/LUG	6.00	12.5	215	935	740/*810	105/*115	1650/*1900	3640/*4190
8.25-20	14	TT	HIW/LUG	6.50	12.5	236	974	740/*810	105/*115	1950/*2240	4410/*4940
9.00-20	14	TT	HIW/LUG	7.00	14	259	1018	690/*760	100/110	2300/*2575	5070/*5675
10.00-20	14	TT	HIW/LUG	7.50	14	278	1055	620/*690	90/*100	2430/*2800	5355/*6175
10.00-20	16	TT	HIW/LUG	7.50	14	278	1055	720/*790	105/*115	2650/*3000	5840/*6610
11.00-20	16	TT	LUG	8.00	16	293	1085	720/*790	105/*115	2900/*3350	6395/*7390
11.00-20	18	TT	LUG	8.00	16	293	1085	840/*910	122/*132	3150/*3650	6945/*8045
12.00-20	20/18	TT	HIW/LUG	8.50	23	315	1125	810/*1125	115/*165	3450/*4000	7590/*8800