

NACCISA TIRE COMPANY,S.A. DE C.V.

CATALOGUE



**AV MUNDIAL #149,MULTIPARK PARQUE CIUDAD APODACA,
NUEVO LEON, C.P. 66633
RFC:NTI2209238J2
TEL:+81 1367 9980 AL 84
FAX:+81 1334 0009**

**ENKIL**
TYRES

High Quality OTR tire

SIZE	PATTERN	PR	TYPE	STANDARD RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATED PRESSURE (KPA)	MAX LOAD (KG)
15.5-25	E-3/L-3	16PR	TL	12.00/1.3	1275	395	225	6750
17.5-25	E-3/L-3	16PR	TL	14.00/1.5	1350	445	475	7300
20.5-25	E-3/L-3	20PR	TL	17.00/2.0	1490	520	450	9500
23.5-25	E-3/L-3	20PR	TL	19.50/2.5	1615	595	375	10900
26.5-25	E-3/L-3	28PR	TL	22.00/3.0	1750	675	475	15500
29.5-25	E-3/L-3	28PR	TL	25.00/3.5	1875	750	425	17500
14.00-24	E-3/L-3	28PR	TL/TTF	10.00W	1370	375	925	10000
16.00-24	E-3/L-3	24PR	TL	11.25/2.0	1495	430	650	10600
20.5/70-16	E-3/L-3NEW	14PR	TL	10.00G	900	318	280	1600
17.5-25	L-5	20PR	TL	14.00/1.5	1400	445	575	8250
23.5-25	L-5	24PR	TL	19.50/2.5	1615	595	475	12500
23.1-26	R-3	12PR	TL	DW20	1500	595	200	5150
15.5-25	G2L2	16PR	TL	12.00/1.3	1275	395	525	6500
17.5-25	G2L2	16PR	TL	14.00/1.5	1330	410	275	3350
13.00-24	G2L2 TG	16PR	TL	8.00TG	1280	335	400	3200
14.00-24	G2L2 TG	16PR	TL	8.00TG	1350	360	375	3650
16.00-24	G2L2	16PR	TL	10.00VA	1460	470	325	4500
16/70-20	R-1 M600	14PR	TL	13.0	1076	407	350	3250
16/70-24	R-1 M600	14PR	TL	13.0	1178	407	350	3550

**E-3/L-3****E-3/L-3NEW****L-5****R-3****G-2/L-2****G-2/L-2 TG****R-1 M600**

**ENKIL**
TYRES

High Quality Industrial tire

SIZE	PATTERN	PR	TYPE	STANDARD RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATED PRESSURE (KPA)	MAX LOAD (KG)
9.00-16	SKS-1	12PR	TL	6.5	920	230	520	3035
10-16.5	SKS-1	10PR	TL	8.25	779	261	520	2170
11L-16	SKS-1	14PR	TL	8.00	838	279	440	1250
12-16.5	SKS-1	12PR	TL	9.75	790	300	550	2900
14-17.5	SKS-1	16PR	TL	10.5	922	351	550	3875
15-19.5	SKS-1	14PR	TL	11.75	1029	391	485	4565
12-16.5	SKS-4	14PR	TL	9.75	790	300	550	2900
27X8.5-15	SKS-5	8PR	TL	7.00	678	213	350	1030
27X10.5-15	SKS-5	10PR	TL	8.5	691	259	340	1090
10-16.5	L5-1	12PR	TL	8.25	779	261	520	2170
12-16.5	L5-1	14PR	TL	9.75	790	300	550	2900
12.5/80-18	L5-1	16PR	TL	9	985	306	370	2625
19.5L-24	L5-1NEW	12PR	TL	17.00	1340	495	230	3455
12.5/80-18	R4-3	16PR	TL	9	978	287	370	2625
19.5L-24	R4-4	12PR	TL	17	1314	495	230	3455
5.00-8	H818	10PR	TTF	3.50D	470	137	1000	1150
6.00-9	H818	10PR	TTF	4.00E	540	160	860	1505
6.50-10	H818	10PR	TTF	5.00F	590	175	790	1655
7.00-15	H818	14PR	TTF	5.5	750	200	860	2870
7.50-15	H818	14PR	TTF	6.0	780	215	790	3075
7.00-12	H818	14PR	TTF	5.00S	676	190	860	2375
28X9-15	H818	14PR	TTF	7.0	710	220	970	3050
8.25-15	H818	14PR	TTF	6.5	840	235	830	3775
240/55D17.5	HCD	16PR	TL	6.75	725	230	735	2800
355/55D625	R-4	20PR	TL	11.75	936	360	560	3450

**SKS-1****SKS-4****SKS-5****L5-1****L5-1NEW****R4-3****R4-4****H818****HCD****R-4**


ENKIL
 TYRES

High Quality Agricultural tire

SIZE	PATTERN	PR	TYPE	STANDARD RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATED PRESSURE (KPA)	MAX LOAD (KG)
5.00-12	R1-1	6PR	TT	4.00E	590	145	200	280
6.00-12	R1-1	8PR	TT	4.50E	640	165	250	405
6.00-14	R1-1	6PR	TT	4.50E	690	165	250	450
6.00-16	R-1Q	8PR	TT	4.50E	745	165	250	495
6.50-16	R-1Q	10PR	TT	5.00F	760	180	250	565
7.50-16	R-1Q	10PR	TT	5.50F	810	205	210	650
7.50-20	R-1Q	10PR	TT	5.50F	910	205	210	760
8.3-20	R1-1	12PR	TT	W7	895	210	240	695
8.3-24	R-1Q	12PR	TT	W7	995	210	240	810
9.5-20	R-1Q	10PR	TT	W8	950	240	280	955
9.5-24	R-1Q	12PR	TT	W8	1050	240	280	1076
11.2-24	R-1Q	12PR	TT	W10	1105	285	180	1045
11.2-28	R-1Q	12PR	TT	W10	1205	285	240	1305
11.2-38	R1-1	12PR	TT	W10	1459	285	120	1055
12.4-28	R1-2	12PR	TT	W11	1260	315	230	1510
13.6-24	R1-3	12PR	TT	W12	1210	345	250	1790
13.6-28	R1-3	12PR	TT	W12	1310	345	250	1910
14.00-38	R1-2	12PR	TT	W12	1565	345	250	2215
14.9-30	R1-2	12PR	TT	W13	1415	378	230	2190
15.5/80-24	R1-2	16PR	TL	W13	1240	394	300	2900
15.5-38	R1-3	12PR	TT	W14L	1570	395	230	2320
16.9-28	R1-2	12PR	TT	W15L	1435	430	200	2380
16.9-30	R1-2	12PR	TT	W15L	1485	430	200	2455
18.4-26	R1-2	12PR	TL	DW16	1450	467	230	2985
11.2-28	Irrigation-2	10PR	TL	W10	1459	285	230	1150


R1-1

R1-2

R1-3

R-1Q

Irrigation-2


ENKIL
 TYRES

High Quality Agricultural tire

SIZE	PATTERN	PR	TYPE	STANDARD RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATED PRESSURE (KPA)	MAX LOAD (KG)
14.9-24	R-1S	12PR	TT	W13	1265	378	260	2000
15.5-38	R-1S	12PR	TT	W14L	1569	394	260	2120
18.4-30	R-1S	12PR	TT	W16L	1552	467	220	2900
18.4-34	R-1S	12PR	TT	W16L	1654	467	220	3000
18.4-38	R-1S	12PR	TT	W16L	1755	467	220	3250
23.1-26	R1-B	12PR	TL	DW20	1605	587	170	3610
30.5L-32	R-1	26PR	TL	DH27	1845	775	280	7100
9.5L-14	I-1	8PR	TL	8.00	741	241	300	1090
11L-14	I-1	8PR	TL	8KB	752	279	250	1100
11L-15	I-1	12PR	TL	W8L	777	279	250	1150
7.50-16	F-2	12PR	TL	5.50F	810	205	370	870
7.50-20	F-2NEW	12PR	TL	5.50F	910	205	370	1020
12.5/80-18	IMP101	12PR	TL	9.00	965	307	370	2650
11L-15	F-3	12PR	TL	8.00	813	279	360	1060
11L-16	F-3	14PR	TL	8.00	838	279	420	1250
26x12.00-12	R-1grass tyre	8PR	TL	10.50	648	307	140	810
29x12.5-15	R-1grass tyre	12PR	TL	10.00	730	330	1080	310
400/60-15.5	I-3	14PR	TL	13*15.5	870	404	360	2900


R-1S

R1-B

R-1

I-1

F-2

F-2 NEW

IMP 101

F-3

R-1 grass tyre

I-3

**ENKIL**
TYRES

High Quality Trailer tire

SIZE	PATTERN	PR	TYPE	STANDARD RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	INFLATED PRESSURE (KPA)	MAX LOAD (KG)
8-14.5	HC301	14PR	TL	6.00	707	203	115	3500LBS
ST 205/75D15	HC303	6PR	TL	51/2J	689	203	50	825
ST 225/75D15	HC303	8PR	TL	6J	719	223	65	1150
10.00-20	HC302	14PR	TTF	7.5	1040	278	100/90	6175/5355
ST 7.00-15 (205/90D15)	HC304	14PR	TL	5.50F	750	200	76	1030
ST7.50-16 (225/90D16)	HC304	14PR	TL	6.00G	850	215	90	1400

**HC301****HC302****HC303****HC304**